


TLR Series

• 105°C 3,000Hrs assured.

- Non-solvent proof
- High Ripple, Wide Temp.
- For SMPS, Inverter.
- RoHS compliant.
- Halogen-free capacitors are also available.



SPECIFICATIONS

Item	Characteristics		
Rated Voltage Range	400 ~ 500 V _{DC}		
Operating Temperature Range	-40 ~ +105°C		
Capacitance Tolerance	±20%(M) (at 20°C, 120Hz)		
Leakage Current	$I = 3\sqrt{CV}$ or 3mA, Whichever is smaller. Where, I: Leakage Current(μA), C: Nominal capacitance(μF), V: Rated voltage(V _{DC}) (at 20°C, 5minutes)		
*Dissipation Factor(Tanδ)	Rated voltage(V _{DC})	400	420 ~ 500
	Tanδ(Max.)	0.15	0.20 (at 20°C, 120Hz)
Temperature Characteristics (Max. Impedance ratio)	Rated voltage(V _{DC})	400	420 ~ 500
	Z(-25°C)/Z(20°C)	4	8
	Z(-40°C)/Z(20°C)	8	16 (at 120Hz)
Load Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 3,000 hours at 105°C Capacitance change ≤ ±20% of the initial value Tanδ ≤ 200% of the initial specified value Leakage current ≤ The initial specified value		
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after the exposing them at 105°C for 1,000hours without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements. Capacitance change ≤ ±20% of the initial value Tanδ ≤ 200% of the initial specified value Leakage current ≤ The initial specified value		
Others	Satisfied characteristics KS C IEC 60384-4		

*For capacitors with CV products >100,000 higher Tanδ value may apply.

When the capacitance exceeds 1,000μF, 0.01 shall be added every 1,000μF increase.

RATED RIPPLE CURRENT


When capacitor are operated in any other condition at 120Hz, the maximum ripple current must be multiplied by the figure shown in the table.

Frequency multiplying factor

V _{DC}	Freq.(Hz)	60	120	300	1k	10k~
400~500		0.77	1.00	1.16	1.30	1.41

DIMENSIONS OF TLR Series

Unit(mm)



RATINGS OF TLR Series

V _{DC}	Capacitance (μF)	øD×L(mm)	Rated Ripple Current (Arms/105°C,120Hz)
400	150	25,4 × 25	1,19
	220	25,4 × 30	1,55
		30 × 25	1,57
	270	25,4 × 35	1,76
	330	30 × 30	2,00
		35 × 25	2,10
	390	25,4 × 50	2,28
		30 × 35	2,29
		35 × 30	2,29
	470	30 × 40	2,60
		35 × 35	2,57
	560	30 × 50	3,10
		35 × 40	3,00
420	680	35 × 45	3,60
	820	35 × 50	3,90
	120	25,4 × 25	1,18
	180	25,4 × 30	1,39
		30 × 25	1,50
	220	25,4 × 35	1,58
		25,4 × 40	1,80
	270	30 × 30	1,80
		35 × 25	1,81
	330	25,4 × 50	2,17
		30 × 35	2,17
	390	35 × 30	2,20
		30 × 40	2,49
	470	35 × 35	2,75
		30 × 50	3,06
	560	35 × 40	3,10
		35 × 45	3,20
	680	35 × 50	3,68

V _{DC}	Capacitance (μF)	øD×L(mm)	Rated Ripple Current (Arms/105°C,120Hz)
450	120	25,4 × 25	1,08
	150	25,4 × 30	1,20
		30 × 25	1,39
	180	25,4 × 35	1,30
		25,4 × 40	1,50
	220	30 × 30	1,50
		35 × 25	1,70
	330	25,4 × 50	1,97
		30 × 40	1,95
	390	30 × 45	2,39
		35 × 35	2,36
	470	30 × 50	2,55
		35 × 40	2,54
500	560	35 × 45	2,68
	680	35 × 50	2,95
	82	25,4 × 25	0,83
	120	25,4 × 30	1,02
		30 × 25	1,02
	150	25,4 × 40	1,20
		30 × 30	1,20
	220	35 × 30	1,52
		25,4 × 50	1,55
	330	30 × 40	1,55
		30 × 45	1,65
	270	35 × 35	1,70
		35 × 40	1,83
	470	35 × 50	1,95